

Inspection upon delivery

Please take a moment to inspect your delivery upon arrival. This helps prevent unexpected issues during installation. Check:

- that the correct products and quantities have been delivered;
- that the packaging and products show no visible transport damage or other damage;
- that any protective film and packaging are still intact.

If any damage or discrepancies are found, take photographs, record them on the delivery note or CMR, and contact us within 2 days of delivery before processing or installing the products.

Unloading and handling

Careful handling helps prevent damage to coatings, edges and components. Please observe the following guidelines:


- Use suitable lifting and handling equipment appropriate for the weight and dimensions of the products;
- Avoid impacts, shocks and unnecessary movement;
- Never drag or slide components over each other;
- Protect edges, corners and visible surfaces during handling;
- Place the materials in a suitable storage location immediately after unloading.

Storage of your materials

Always store your materials in a clean, dry location and protect them from the weather as much as possible. Follow the storage instructions that apply to your specific product.

General:

- Process and install the materials within one month after shipment to maintain product quality;
- Store materials on a flat, clean and dry surface;
- Avoid exposure to moisture, dirt and direct sunlight;
- Use a breathable cover when protecting stored materials;
- Check regularly for moisture and condensation.



Product-specific:

- Flat steel cladding and sandwich panels: Store with a slight slope (minimum 5°) to allow water to drain away;
- Curved sheets / curved steel cladding: Store and cover in such a way that water cannot collect in the curve; always use a breathable cover;
- Structural steel components, doors and profiles: Store in a dry, protected location and prevent damage to edges, corners and finished surfaces;
- Structural steel components: Repair any primer damage and uncoated contact areas before or during installation using the supplied primer. Slight colour differences may occur;
- Screws and loose fasteners: Store in a dry place, preferably in the original packaging.



Before processing and installation

Before processing and installation, check that all materials are clean, dry and undamaged. Also observe the following:

- Remove the protective film as soon as possible and no later than one month after delivery. Earlier removal may be necessary when exposed to direct sunlight or high temperatures;
- Do not process or install materials showing signs of moisture, condensation, contamination or damage;
- Failure to follow these instructions will void the product warranty;
- If you have any questions about the condition of a product or the correct processing method, please contact us first. We will be happy to assist you.

