



Applications:

Our steel corrugated sheets type 18/76 are used for both roof and wall cladding in steel buildings, halls, sheds, and industrial buildings. Thanks to their low weight and efficient profile, the sheets are suitable for new construction, renovation, and extensions. The sheets are provided with a durable polyester coating and CE marking, and are optionally available as translucent sheets, with anti-condensation fleece, or perforated.

Technical data:	760 mm:	988 mm:
Sheet thickness	0,56 mm	0,56 mm
Total width	835 mm	1063 mm
Effective width	760 mm	988 mm
Overlap	76 mm	76 mm
Profile height	18 mm	18 mm
Wave radius	24 mm	24 mm
Length	1000 - 8000 mm	1000 - 8000 mm
Bending radius	> 3000 mm	> 3000 mm
Weight with overlap	5.4 kg/m ²	5.2 kg/m ²
Weight without overlap	4.9 kg/m ²	4.9 kg/m ²

Additional information:	
Galvanized	ZM100 / Z225
Silicone polyester coating	Inside: 5-10 µm (RAL 9002) Outside: 25 µm (14 Std. colors)
Optional	Perforated (RAL9002) Anti-condensation fleece

Version: 10/2025

Remark: The values in this datasheet are intended as guidelines. No legal commitment can be derived from them.

